HP-S3 Reusable Earplugs

Metal-Detectable

NRR 23 dB



Easy to Dispense



Convenient clip-on carrying case

Features:

The **HP-S3** is a **metal-detectable,** reusable extra soft triple-flange, yellow earplug. Made from high-quality 100% silicone material. These earplugs are hypoallergenic, lightweight and provide a low-pressure comfortable seal. The triple-flange design provides a snug fit while gently conforming to the ear canal. NRR 23 dB.

Benefits:

- Environmentally-friendly 100% silicone earplugs
- Reusable metal-detectable earplugs
- Extra-soft, lightweight silicone seals the ear canal without pressure
- Triple-flange shape with firm handle provides an easy to insert, snug fit while gently conforming to the ear canal
- Manufactured through vulcanization, not mold injected for the ultimate flexibility
- Hypoallergenic and non-irritating
- High-visibility yellow color
- Packaged 1 pair per personal clip-on carrying case

Applications:

- Airport Crews
- Pulp and Paper
- Automotive
- Landscaping
- Printing
- Utilities
- Food Processing
- Mining
- Contracting
- Construction
- Petrochemical
- Waste Management

Ordering Information:

Item No.: **HP-S3 Corded**

Each unit: 1 Pr/Rectangle Plastic Case

Inner unit: 100 Pr/Dispenser Box

Master Case: 10 Dispenser Boxes/Case (1,000 Pairs)

Barcode Information:

Each: 810292029623

Inner: 10810292029620

Case: 20810292029627

ANSI S3.19-1974 sound attenuation data:

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean Attenuation (dB)	28.7	25.9	31.3	27.3	35.1	39.4	40.3	46.2	46.2	23 dB
Standard Deviation (dB)	5.5	4.5	4.5	2.8	4.3	4.2	5.6	6.1	3.7	

EN 352-2: 2002 sound attenuation data:

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Sound Attenuation (dB)	29.6	28.3	30.1	28.8	34.6	38.9	44
Standard Deviation (dB)	5.6	6	7.8	6	3.9	5.6	5.6
Assumed Protection (dB)	24	22.3	22.3	22.8	30.7	33.3	38.4

SNR = 28 dB, H = 30 dB, M = 24 dB, L = 23 dB

Bullhead Safety®
13915 Radium St. NW
Ramsey, MN 55303
www.bullheadsafety.com

Phone: 763-450-0110

Sales@Bullheadsafety.com